## **LED Digital Poster**



## Your signage where you want it

Capture attention and make your brand memorable with vibrant mobile signage Simple content streaming with wired or wireless connection from your input devices Showcase the Posters individually or stack them to create a dynamic, affordable Video Wall

Crisp, bright, vivid visuals with a pixel pitch of just 1.9 mm



Specifications			
Model	LED Poster 72"	IP Rating	IP30
Diagonal Length (in)	72"	Input Voltage	100~240 VAC 50/60 Hz
Pixel Pitch (mm)	1.9 mm	Installation Type	Stand
Display Size (in)	24" x 67.5"	Maintenance Type	Front Access
Overall Size (Width x Height) (in)	24.5" x 68.1" x 1.3"	Operating Temperature / Humidity	-10°~40° / 10%~80% RH No condensation
Power Consumption (Max / Average) (W)	560W / 200W	Connectivity	LAN, Dual Frequency Wi-Fi (2.4 GHz & 5 GHz)
Weight (lbs)	83.7 lbs	Connectivity	Bluetooth Supported
LED Type	SMD standard or with Glue-on-board (GOB) coating	CPU	Quad-core Processor upto 1.8 Ghz (4x A55)
Brightness (nits)	800 nits	Storage	16 GB
Refresh Rate (Hz)	3840 Hz	RAM	1 GB
Resolution	320 x 900	Input Ports	1x RJ 45, 1x HDMI In, 1x USB 3.0
Cabinet Size (Width x Height) (in)	24" x 13.5"	Output Ports	1x HDMI Out, 1x Audio Out (for external speakers)
Cabinet Material	Die-cast Magnalium	Supported Media	Support mainstream video format such as MPEG1,
Gray Scale (Bit)	13~16 bit		MPEG2, MPEG4, WMV, MKV, TS, and flv; Support audio formats such as MP3; Support JPG, JPEG, BMP, PNG,
Viewing Angle (Deg)	170/170 (Horizontal / Vertical)		GIF and other image format

Software and Support	
Screen Mirroring Software	Wireless sharing from up to 4 simultaneous connected devices
Support	24/5 Free, unlimited support and training via email / phone / app

